



## Felge                      Einspeichdurchmesser

V 2.8

(Maulweite)                      (Nippelsitz zu Nippelsitz)

|                    | Größe - x mm<br>ohne Ösen | Größe - x mm<br>Einzelöse (-1mm) | Größe - x mm<br>Doppelöse (-2mm) |
|--------------------|---------------------------|----------------------------------|----------------------------------|
| Alpha 19           | -30,0                     | -29,0                            | -28,0                            |
| Alu Reflex 19      | -27,5                     | -26,5                            | -25,5                            |
| Craft 21           | -20,0                     | -19,0                            | -18,0                            |
| Craft 30           | -29,0                     | -28,0                            | -27,0                            |
| Craft 35           | -28,0                     | -27,0                            | -26,0                            |
| Cross 19           | -6,0                      | -5,0                             | -4,0                             |
| Downhill 25        | -24,8                     | 23,8                             | 22,8                             |
| ESR                | -17,0                     | gepunzt -18,0                    | ---                              |
| Eurodisk 17        | -18,0                     | -17,0                            | -16,0                            |
| Euroline 19        | -34,0                     | ---                              | ---                              |
| Euroreflex 19      | -35,0                     | ---                              | ---                              |
| Gravel 19          | -43,0                     | ---                              | ---                              |
| Gravel 21          | -43,0                     | ---                              | ---                              |
| LXS 17             | -23,8                     | -22,8                            | -21,8                            |
| Point 19           | -14,0                     | ---                              | ---                              |
| SDR 19             | ---                       | -19,0                            | -18,0                            |
| SDR 19 light       | -23,0                     | -22,0                            | -21,0                            |
| SDR 21             | -23,0                     | -22,0                            | -21,0                            |
| SDX 19             | 22,5                      | 21,5                             | 20,5                             |
| SDX 21             | -15,0                     |                                  |                                  |
| Sport 16           | -12,0                     | -11,0                            | ---                              |
| Sport 19           | -12,0                     | -11,0                            | ---                              |
| Sport 21           | -13,0                     | -12,0                            | ---                              |
| Sport 25           | -12,0                     | -11,0                            | ---                              |
| Sportivo 19        | -30,0                     | -29,0                            | -28,0                            |
| Sprint 19          | -16,0                     | -15,0                            | -14,0                            |
| Star 19            | -27,5                     | -26,5                            | -25,5                            |
| Starline 19        | -26,0                     | -25,0                            | -24,0                            |
| Starline Reflex 19 | -26,0                     | -25,0                            | -24,0                            |
| Tour 21            | -21,0                     | -20,0                            | -19,0                            |
| Tour DX 19         | -22,0                     | -21,0                            | -20,0                            |
| Tour RS 17         | -25,0                     | -24,0                            | -23,0                            |
| Tour SX 19         | -22,0                     | -21,0                            | -20,0                            |
| Westwood 24        | -12,0                     | ---                              | ---                              |
| Yak 19             | -17,0                     | -16,0                            | -15,0                            |
| Yak 21 Disc        | -17,5                     | -16,5                            | -15,5                            |
| Yak 23 Disc        | -17,5                     | -16,5                            | -15,5                            |
| Yak 25 Disc        | -17,5                     | -16,5                            | -15,5                            |
| ZXS 19             | -26,4                     | -25,4                            | -24,4                            |

Für die Berechnung des Einspeichdurchmessers benutzen Sie bitte folgende Formel: Felgenreöße - X-Maß = Einspeichdurchmesser  
 Beispiel für eine Felge Euroline 622 (28"): 622mm - 35mm = 587mm ED  
 Alle Angaben ohne Gewähr